



nLTS™-(vc)2UE

SimulCharge 2 x USB 2.0 and Ethernet adapter with an optional Voltage Converter

- Simultaneous data and charging
- 2 x USB-A ports for connecting accessories
- 10/100 Ethernet (LAN) Network
- Lenovo tablet and USB accessories charging at the same time
- Available with an optional built-in voltage converter







Product Description

The nLTS-(vc)2UE adapter for Lenovo tablets features wired Ethernet connectivity, Simulcharge technology that lets tablets to operate as a USB Host controller while simultaneously being charged.

This adapter includes two USB 2.0 (Type-A) ports for connecting two additional USB peripherals.

The adapter comes with a casing and Micro USB to Micro USB cable to connect the tablet.

The nLTS-2UE uses a standard USB power supply provided with the tablet. The nLTS-vc2UE version offers built-in voltage converter that allows an external 11 V up to 36 V DC power supply to be placed up to 50 ft. away from the tablet. The power supply is not included.

 <p>SimulCharge</p>	<p>The uLTS-2UE operates a tablet in SimulCharge mode. This technology allows the charging of the Lenovo Micro USB tablets while interacting with USB accessories.</p>
 <p>Ethernet</p>	<p>The uLTS-2UE features a 10/100 Fast Ethernet interface that enhances the reliability and security of the internet connection. The tablet can use the dynamic address (DHCP) or static address for the network communication.</p>
 <p>2 x USB-A Ports</p>	<p>LAVA adapters allow a tablet to be integrated into a kiosk installation with multiple USB devices such as barcode scanners, printers, payment terminals, and other USB-enabled peripherals.</p>
 <p>11-36 VDC In</p>	<p>Allows an external 11 V - 36 V DC power supply to be placed up to 50 feet away from the tablet and not be limited by standard charger cable lengths.</p>

SYSTEM REQUIREMENTS

Tablet:	Select Lenovo Micro USB tablets. Please refer to the tested tablet list that can be found at www.lavasimulcharge.com	
Power Supply:	USB Charger/Power Supply with a Micro USB-B connector, such as the power supply provided with the tablet. Any regulated 5 volt power supply capable of at least 2 amperes can be used. When using the optional Barrel Jack, an unregulated 12V up to 24V DC power supply is recommended.	
Ports/Connectors:	1 x RJ45 10/100 Ethernet port (LAN) 1 x Micro USB-B port (for Tablet connection) 1 x Micro USB-B port (the 5V power input) 2 x USB 2.0 ports for connecting peripherals	1 x Charge State LED 1 x Ethernet Link indicator LED 1 x Tablet USB indicator LED OPTIONAL: 1 X Barrel (2 mm) DC Output Connector (Centre Pin Positive)
Cables:	1 x Micro USB B to Micro USB B cable (3.3ft / 1m)	
Measurements:	Depth: 3.3 inches (83 mm) Width: 3.8 inches (97 mm)	Height: 1.7 inches (44 mm) – with standoffs Weight: 4.1 oz