



nSTS-1U-OEM

1-PORT SIMULCHARGE™ USB ADAPTER WITH DOCKING DETECT FOR SAMSUNG TABLETS

PRODUCT DETAILS

The nSTS-1U-OEM is an adapter for Samsung tablets* that features one USB 2.0 (Type-A) port, Simulcharge technology that lets tablets charge and at the same time support USB peripherals, and the newest LAVA development adds Docking Detect for automatic tablet and LAVA board connection.



APPLICATION

The nSTS board is ideal for situations where tablets need power and the ability to support USB accessories in a situation when power sequences cannot always be followed. If you intend to plug your tablet solution in and out of power often, this board will meet your installation requirements.



The nSTS-1U-OEM operates a tablet in SimulCharge mode. This technology allows the charging of the selected Samsung tablets while interacting with USB accessories.



The Docking Detect feature ensures that when the adapter is plugged into the tablet, the tablet recognizes that the adapter is present. This feature is a re-imagined form of Plug-n-Play; when the tablet solution, the tablet along with the adapter, is plugged into or out of power, the tablet will know.



LAVA adapters allow a Samsung tablet to be integrated into a kiosk installation with multiple USB devices such as magnetic card readers, NFC readers, printers, barcode scanners, keyboard, and other USB-enabled peripherals.

PRODUCT FEATURES

- › Simultaneous USB host and charging for selected Samsung tablets
- › Docking detect for a tablet connection
- › Designed for commercial/OEM use with Samsung tablets (see compatibility list of supported devices)
- › Works with out-of-the-box (unrooted) tablets
- › Powered by a standard USB Charger/Power Supply through a Micro USB-B receptacle
- › Can be powered by a USB Battery Pack (aka Power Bank)
- › Prevents power drain from the tablet to USB peripherals in the event of power loss
- › 1 x USB 2.0 port
- › LAVA Limited Warranty

SYSTEM REQUIREMENTS

Tablet:	Please refer to the tested tablet list that can be found at www.lavalink.com	
Power Supply:	USB Charger/Power Supply with a Micro USB-B connector, such as the power supply provided with the Galaxy tablet. Any regulated 5 volt power supply capable of at least 2 amperes can be used.	
Ports/Connectors:	1 x USB A port (for USB 2.0 accessories) 1 x Micro USB B port (for Tablet connection) 1 x Micro USB B port (the 5V power input)	1 x Charge State LED
Cables:	1 x Micro USB B to Micro USB B cable (8"/20 cm) Note: The custom 8"/20 cm cable connects the device to the tablet. This cable may not be extended.	
Measurements:	Depth: 1.69 inches (42 mm) Width: 1.26 inches (32 mm)	Height: 0.44 inches (15 mm) Weight: n/a

LAVA Computers MFG. Inc. designs and manufactures computing interfaces and devices for the Point of Sale, Kiosk, Gaming, Industrial Automation, Security and Access Control industries, and has been doing so since 1984. As experts in serial interfaces for PCI, PCIe, ISA, USB, and Ethernet buses, LAVA builds tablet PoE/USB/LAN devices, Ethernet-to-serial device servers, serial/parallel I/O boards, and embedded IoT/M2M connectivity devices.

With over a million LAVA products built into workstations, servers, retail POS systems, and industrial computers, LAVA products are trusted by resellers, distributors, OEMs and system builders in over 47 countries worldwide.

